

Prelude Correlator - Bug #355

problem between daemon and pid file options

06/18/2009 03:07 PM - Pierre Chifflier

Status:	Resolved	Start date:	06/18/2009
Priority:	Normal	Due date:	
Assignee:	Yoann VANDOORSELAERE	% Done:	100%
Category:		Estimated time:	0.00 hour
Target version:	0.9.0-beta5		
Resolution:			

Description

When I try to start the correlator in daemon mode, specifying the pid file, it doesn't start (the pid file exists and is writable by the user).

```
$ /usr/bin/prelude-correlator -d -P /var/run/prelude-correlator.pid
$ ps axf |grep prelude-correlator |wc -l
0
```

Strace shows something weird in the code:

```
$ strace -s 256 -f /usr/bin/prelude-correlator -d -P /var/run/prelude-correlator.pid
[...]
[pid 12080] write(2, " File \"/usr/lib/pymodules/python2.5/PreludeCorrelator/main.py\"", line 147,
in main\n", 83) = 83
[...]
[pid 12080] write(2, " ", 4) = 4
[pid 12080] write(2, "open(pidfile, \"w\").write(str(os.getpid()))\n", 43) = 43
[pid 12080] close(3) = 0
[pid 12080] munmap(0x7f1c86a02000, 4096) = 0
[pid 12080] write(2, "NameError", 9) = 9
[pid 12080] write(2, ": ", 2) = 2
[pid 12080] write(2, "global name 'pidfile' is not defined", 36) = 36
```

PS: logging the output to syslog would be a nice feature wink.png

Associated revisions

Revision 5491e092 - 06/18/2009 03:21 PM - Yoann VANDOORSELAERE

Correct invalid variable name.

This prevented prelude-correlator from starting in daemon mode when using the '--pidfile' option. Fixes #355.

History

#1 - 06/18/2009 03:32 PM - Yoann VANDOORSELAERE

- Status changed from New to Assigned
- Assignee set to Yoann VANDOORSELAERE
- Target version set to 0.9.0-beta5

#2 - 06/18/2009 03:33 PM - Yoann VANDORSELAERE

- *Status changed from Assigned to Resolved*

- *% Done changed from 0 to 100*

Applied in changeset [5491e0920a4fc71263a7a9c9dd2bf38dd2baceb5](#).