

## Libprelude - Feature #13

### Provide the ability for the user to define the analyzer configuration file

06/03/2004 10:09 AM - Yoann VANDOORSELAERE

<b>Status:</b>	Closed	<b>Start date:</b>	
<b>Priority:</b>	High	<b>Due date:</b>	
<b>Assignee:</b>	Yoann VANDOORSELAERE	<b>% Done:</b>	0%
<b>Category:</b>		<b>Estimated time:</b>	0.00 hour
<b>Target version:</b>			
<b>Resolution:</b>	fixed		

#### Description

Currently each analyzer hardcode access to it's own configuration file. We need to add a 'config-file' command line option, overriding default hardcoded analyzer configuration file.

In combination with ticket [#12](#), this will allow to have several analyzer instance running with their own independant configuration.

#### History

##### #1 - 06/03/2004 02:12 PM -

This (and [#12](#) as well) has been already been implemented manually in the Snort sensor (I was told that people ~~de~~ run multiple Snort instances) by letting the user specify values passed to `prelude_sensor_init()`, hence this possibility should not be removed. Additionally `libprelude` cannot parse Snort's command line directly so care should be taken with including any functionality requiring access to the command line.

##### #2 - 06/03/2004 02:19 PM - Yoann VANDOORSELAERE

The workaround you are describing here is a common workaround which work well for sensor not depending upon `prelude-getopt`. The point of this ticket is to make the fonctionnality available to anyone who want to use it (things won't be broken for sensors not using `prelude-getopt`).

##### #3 - 06/06/2004 11:51 PM - Yoann VANDOORSELAERE

- Status changed from New to Assigned

##### #4 - 06/11/2004 12:21 AM - Yoann VANDOORSELAERE

- Status changed from Assigned to Closed

- Resolution set to fixed

Fixed in r3717

##### #5 - 04/29/2009 12:26 PM - Yoann VANDOORSELAERE

- Project changed from PRELUDE SIEM to Libprelude

- Category deleted (1)