

Libprelude - Feature #255

Profiles should work with chrooted environments

08/21/2007 11:17 AM - Sebastien Tricaud

Status:	Closed	Start date:	
Priority:	High	Due date:	
Assignee:	Sebastien Tricaud	% Done:	0%
Category:		Estimated time:	0.00 hour
Target version:	0.9.21		
Resolution:	fixed		
Description			
When adding an analyzer profile, that will go straight to PRELUDE_CONFIG_DIR. There must be a way to for forcing it being located somewhere else.			

History

#1 - 02/28/2008 03:03 PM - Pierre Chifflier

On a more general way, having a config option for the profile dir would be really nice ! Actually, this is configured at build time, which is not convenient.

On runtime, it would be nice to configure the location at runtime using, for ex, one of:

- command line option
- config (?) option
- environment variable

Pierre

#2 - 09/15/2008 12:31 PM - Yoann VANDOORSELAERE

- Status changed from New to Closed

- Resolution set to fixed

(In r10995) Implement prelude_client_profile_get_default_config_dirname(), and prelude_client_profile_set_prefix().

Modify prelude-admin so that it always use prelude-client-profile function in order to retrieve libprelude specific path.

Use the relocatable module from prelude-client-profile in order to relocate path when needed.

This fix [#255](#).

#3 - 04/29/2009 12:25 PM - Yoann VANDOORSELAERE

- Project changed from PRELUDE SIEM to Libprelude

- *Category deleted (1)*
- *Target version deleted (0.9.21)*