

Prelude Correlator - Feature #298

Example init.d script for prelude correlator

07/10/2008 09:31 AM - Pierre Chifflier

Status: Resolved	Start date:
Priority: Normal	Due date:
Assignee:	% Done: 0%
Category:	Estimated time: 0.00 hour
Target version:	
Resolution:	
Description	
<p>Here is the debian init.d script I wrote for Prelude Correlator. It uses standard LSB functions (which are not Debian specific) and start-stop-daemon, so it should work on other distros with the same tools.</p> <p>The script can be re-used for other Prelude components, just by replacing the name correlator.</p> <p>Note: it reads a file <code>/etc/default/prelude-correlator</code> and uses some variables. Here is the Debian default file:</p> <pre>DAEMONUSER=prelude-correlator # Users to run the daemons as. RUN=yes # set to yes to start the server in the init.d script. # you need to register the "prelude-correlator" profile # before being able to start the correlator automatically</pre> <p>HTH, Pierre</p>	

History

#1 - 09/17/2008 06:47 PM -

Hi,

Thanks for the effort. You should not do an "exit 0" without any message at all. It took me sometime to discover what the hell was going on.

One more time, thanks for posting the script.

#2 - 04/29/2009 12:20 PM - Yoann VANDOORSELAERE

- Project changed from PRELUDE SIEM to Prelude Correlator

- Category deleted (11)

#3 - 03/02/2016 10:28 AM - Antoine LUONG

- Description updated

- Status changed from New to Resolved

Files

prelude-correlator.init	8.95 KB	07/10/2008	Pierre Chifflier
-------------------------	---------	------------	------------------