

## Prewikka - Bug #339

### browse event at relying node

12/15/2008 07:03 PM -

<b>Status:</b>	Closed	<b>Start date:</b>	
<b>Priority:</b>	Normal	<b>Due date:</b>	
<b>Assignee:</b>		<b>% Done:</b>	0%
<b>Category:</b>		<b>Estimated time:</b>	0.00 hour
<b>Target version:</b>	0.9.15		
<b>Resolution:</b>	fixed		

#### Description

Hi,

I've configure Prelude IDS with relaying support and I'm having some problems on accessing the event at the relayed node, for instance I generate an event on node1, with prewikka I can access to that information, but when I try to access at the relayed node it throws this error (see attach).

I'm defining the field in prelude-correlator like this:

```
ctx:set("alert.correlation_alert.alertident(>>).alertident", INPUT:getraw("alert.messageid"))
```

Any help would be appreciated.

--

Rui

#### History

##### #1 - 12/15/2008 07:12 PM -

It was marked as spam so the attach doesn't work and inline too. So I put it on a web page: <http://estudass.es/~rpvilao/error.html>

##### #2 - 12/23/2008 09:21 AM - Yoann VANDOORSELAERE

- Status changed from New to Closed

- Resolution set to fixed

(In r11103) Invalid variable name, fix [#339](#).

##### #3 - 04/29/2009 02:57 PM - Yoann VANDOORSELAERE

- Project changed from PRELUDE SIEM to Prewikka

- Category deleted (generic)

- Target version deleted (80)

##### #4 - 04/30/2009 01:37 PM - Yoann VANDOORSELAERE

- Target version set to 0.9.15