

## Libprelude - Bug #893

### libprelude-errors failed compile on hurd-i386

06/24/2017 02:23 PM - Thomas ANDREJAK

<b>Status:</b>	New	<b>Start date:</b>	06/24/2017
<b>Priority:</b>	Normal	<b>Due date:</b>	
<b>Assignee:</b>		<b>% Done:</b>	0%
<b>Category:</b>		<b>Estimated time:</b>	0.00 hour
<b>Target version:</b>			
<b>Resolution:</b>			
<b>Description</b>			
<pre>make[6]: Entering directory '/&lt;&lt;PKGBUILDDIR&gt;&gt;/src/libprelude-error' LANG="" gawk -f ./mkstrtable.awk -v textidx=3 \   ./err-sources.h.in &gt;err-sources.h LANG="" gawk -f ./mkstrtable.awk -v textidx=3 \   ./err-codes.h.in &gt;err-codes.h LANG="" gawk -f ./mkerrcodes1.awk ./errnos.in &gt;_mkerrcodes.h gcc -E -P _mkerrcodes.h   grep PRELUDE_ERROR_   LANG="" gawk -f ./mkerrcodes.awk &gt;mkerrcodes.h rm _mkerrcodes.h gcc -g -O2 -fdebug-prefix-map=/&lt;&lt;PKGBUILDDIR&gt;&gt;=. -specs=/usr/share/dpkg/pie-compile.specs -fstack- protector-strong -Wformat -Werror=format-security -I. -I. -o mkerrcodes ./mkerrcodes.c In file included from ./mkerrcodes.c:26:0: ./mkerrcodes.h:3:3: error: expected identifier or '(' before numeric constant   ((0x10 &lt;&lt; 26)   ((7) &amp; 0x3fff)) PRELUDE_ERROR_E2BIG     ^~~~ ./mkerrcodes.h:3:15: error: expected ')' before ' ' token   ((0x10 &lt;&lt; 26)   ((7) &amp; 0x3fff)) PRELUDE_ERROR_E2BIG     ^ ./mkerrcodes.c: In function 'main': ./mkerrcodes.c:59:31: error: 'err_table' undeclared (first use in this function)     for (i = 0; i &lt; sizeof (err_table) / sizeof (err_table[0]) - 1; i++)                           ^~~~~~ ./mkerrcodes.c:59:31: note: each undeclared identifier is reported only once for each function it appears in Makefile:1790: recipe for target 'mkerrcodes' failed</pre>			